

EPOS Litchi Pro

L1610 / L1611 / L1612



Food & Beverage



Fashion & Retail



Supermarket



GMS Certified
Android 14



Octa-Core
Processor



15.6" FHD
Touch Screen



Faster
Connectivity



Seamless
Pairing

EPOS

www.paxtechnology.com



MAXSTORE

EPOS Litchi Pro

L1610 / L1611 / L1612

SPECIFICATIONS

	Operating System	Android 14, GMS Certified, Supporting UNIPHIZ UI
	Processor	Octa-Core Cortex A72 2.2GHz NPU: 6TOPS
	Memory	4GB DDR RAM + 64GB eMMC Flash Optional: 8GB DDR RAM + 128GB eMMC Flash External: microSD Card Slot Up to 256GB
	Cameras	Merchant Facing Camera: 5MP Auto Focus (for L1610) Customer Facing Camera: 5MP Auto Focus (for L1611& L1612)
	Displays	Main Display: 15.6" 1920 × 1080 Pixels IPS Touch Screen Customer Facing Display: L1610: not available L1611: 10.1" 1280 × 800 Pixels IPS Touch Screen L1612: 15.6" 1920 × 1080 Pixels IPS Touch Screen
	Comms Configurations	Wi-Fi 6 Bluetooth 5.0
	Audio	Speaker: 3W Microphone
	Card Readers	NFC on the Secondary Screen (Card Reader, Card Emulation)
	SAM	Optional: 1 SAM (only available for L1611)
	Buttons	Power Button
	Ports	1 Type-A 3.0 3 Type-A 1 Type-C 3.0 1 LAN (1000M) 1 DK (RJ11, 24V / 12V) 1 RS232(RJ45) DC IN Audio Jack
	Power	Input: 100-240V AC, 1.0A Output: 24V DC, 1.5A
	Power Indicator	White LED
	Physical	364.6 × 220.0 × 322.4mm L1610: 5kg L1611: 6kg L1612: 7kg
	Environmental	Operating Temperature: 0°C ~ 50°C (32°F ~ 122°F) Storage Temperature: -20°C ~ 60°C (-4°F ~ 140°F) Relative Humidity: 10% ~ 93%, Non-Condensing

L1610



L1611



L1612

